# Act II: Testing UAr in SCENE

Weekly Update 12/17/14

**Thomas Alexander** 


#### Run Overview

- Began filling Dec 13<sup>th</sup>, with first data runs beginning at 1:42 AM December 14th. S1 only data, liquid level above face of TOP PMT. Vigorous recirculation, 6 slm with the heater on the bottom at 27W.
- S2 data collection began 26 hours later. Vigorous recirculation continued while data was collected for 16 hours, then recirc was dropped down to 3 slm, 3W. Finally, bottom heater was turned off completely for 4 hours.
- Following disappointing signal with a calm TPC, studied liquid level issues for about an hour, decided against adding gas and began recirculation at 3slm/3W.
- Deciding to focus on data analysis rather than collection, vigorous (6slm/27W) recirculation resumed for 13 hours.
- Anode was turned off and S1 only data was taken, with the drift varying.
   Liquid level was at S1+S2 levels.

### Analysis Method


- Identify 83Kr peak in S1 by finding highest bin, then fit a Gaussian 60 PE in both directions.
- Using that identified peak, select S2 events based on drift time, S1 Signal. Account for skew of events near the bottom.
- For those 83Kr events, plot drift time vs S2 signal
- Fit gausians to slices along the S2 axis to find the mean of each S2 peak.
- Fit an exponential across those means to find the electron drift lifetime.

## Light Yield




### Light Yield Across Runs

Light Yield (PE)





### Electron Drift Lifetime Across Runs




### Electron Drift Lifetime

Example from Run000143
Lifetime = 100 +/- 1 microseconds








### Vs Atmospheric Run...


Lifetime = 122 +/- 4 microseconds


Much smaller S2 signal, but better light yield. I believe this to be an Operator Error. I did not want to be adjusting the liquid level while I was watching the lifetime improve. I also didn't want to just use UAr willy-nilly.




# Long Drift run (Drift V=50V/cm)

Lifetime = 87.8 microseconds







### Ongoing work...

- As I said, the Light Yield's are bound to a bit of change. I did not have time to preprocess each run with it's unique SPE\_mean calculation.
- Still need triplet state lifetime from AverageWaveforms. Ongoing...

These plots could be a bit more precise! Sorry. I need to show when I change the recirculation environment.

#### Conclusion

- Bottle UAr #3 was used to test the viability of the UAr in a dual-phase TPC.
- Both Scintillation and Ionization has been observed in the first 50 Hours that is similar to a previous run using atmospheric argon
- Zirconium gettering appears to be effective method of cleaning the argon